



Declaration of Performance (DoP)

DoP No.: 004-DM-V-CPR/4454/2013-05-30

1. Product Name:

Unique identification code of the product-type:

Fondaline 400

2. Product Type:

Number allowing identification of the construction product as required under Article 11(4) of the CPR:

Fondaline 400

(lot no. see label and product)

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

for damp proof sheets, type V

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

ONDULINE

35 rue Baudin

92593 Levallois

Cedex (France)

Tél : 01 55 63 80 10 – Fax : 01 41 34 30 54

www.onduline.com

5. Where applicable, name and **contact address** of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. AVCP:

System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:

System 2+

7. Notified body:

1213

In case of the declaration of performance (DoP) concerning a construction product covered by the harmonized standard:

EN 13967:2012

Notified body SKZ – TeConA GmbH (identification no. 1213) performed the initial inspection of the manufacturing plant and of factory production control (FPC) and the continuous surveillance, assessment and evaluation of FPC and issued the certificate of conformity of the FPC no. 4454



8. Declared performance

Essential characteristics	U.M.	Performance	Test standard	Harmonised technical specification
Water tightness (60 kPa, 24 h)	-	Pass	EN 1928,	EN 13967:2012
Tear resistance MD	N	npd	EN 12310-1	
Tear resistance CMD	N	npd	EN 12310-1	
Joint tensile shear resistance	N/50mm	npd	EN 12317-2	
Resistance to impact	mm	<450	EN 12691-2, Method A	
Tensile strength MD/CMD	N/5cm	>200/>200	EN 12311-2	
Elongation MD/CMD	%	>20/>25	EN 12311-2	
Resistance to static load	kg	npd	EN 12730	
Reaction to fire	-	Class F	EN ISO 11925-2, classification to EN 13501-1	
Resistance against ageing	-	Pass	EN 1296 / EN 1928	
Chemical resistance	-	npd	EN 1847 / EN 1928	

9. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Jean Noël FOUREL
CEO ONDULINE

Levallois Perret, 01/07/2013